



## HOP20C

### HAND OPERATED OIL PUMP

- Output capacity : 40cc / stroke
- Capacity : 20 Liters

\* **Optional Accessory**

## HOP-G

### HAND OPERATED OIL PUMP ACCESSORIES

- Connections Size : 1/2"pt
- Pressure : 128 kg/cm<sup>2</sup> (125 bar)
- Temperature : -10°C~ +50°C
- Viscosity : 8-2000 mpas
- Weight : 0.6kg



## HGP20

### 20L HAND GREASE PUMP

- Capacity : 5Gallon
- Output Capacity : 3.2g / stroke
- Output Pressure : 250kg / cm<sup>2</sup>



## OC70

### 70L VENTURI SYSTEM OIL EXTRACTOR

- Waste Oil Mobile reservoirs to be used for motor and gear collection.
- Drainers can be used under vehicle lifts or inside lubrication pit.
- Large handle for easy maneuverability.
- Two brake wheels (Φ3") and two casters (Φ3")
- Extra large drain bowl / Adjustable collecting bowl / For the convenient and safe collection.

#### Specification:-

|              |                        |
|--------------|------------------------|
| Dimension    | : 600x600x1390m/m      |
| Capacity     | : Chamber:10L Tank:60L |
| Weight       | : 28.84 kgs            |
| Power        | : Air                  |
| Oil Draining | : Air Pressure         |



## WOR80

### 80L WASTE OIL RESERVOIR

#### Specification:

- Heavy duty 15" x 5.5"
- Receiver funnel
- Extends from 46" to 70"
- Two 6" fixed axle wheels
- Two swivel casters for maximum maneuverability.
- 8" discharge hose with shut off valve
- Fluid level gauge is on the hose
- Air pressure valve

\*Picture shown are for reference only



### TFS-K10A K10A-2 TRANSMISSION FILLING SYSTEM

- Manually operated oil dispensing unit manufactured from composite materials.
- Large visual measurement will identify amount dispensed.
- Supplied with a range of five automatic transmission fluid adaptors.
- Features a fluid control valve and adaptor stowage to minimise oil leakage when not in use.
- Supplied with a 1.8m hose connected to a special connecting nozzle.
- Complete with a set of special adapting nozzle(8 units) for modern vehicles such as : VW, Audi, Benz, Ford, etc.



### TFS601 TRANSMISSION FILLING SYSTEM

- Capacity : 7.5L
- Outlet: 80cc / cycle
- Viscosity Range: up to SAE140



### LD6115 PNEUMATIC OIL & LIQUID DISPENSER

- 6000cc 2 In 1 Extract & pump Dispenser.
- With 1M Nylon Hose Extracting oil Tank.
- 1.2m Pu Hose With Super Flexible Rubber Nozzle.
- Fixing Valve & Safty Cup For Automatic Cut-Off Extract.
- Suitable For Narrow & Difficult Space Filling.
- Simple And Easy To Operate Suitable Extracting & Filling Any Liquid.

#### Specifications:

|                   |                |
|-------------------|----------------|
| Air Inlet         | : 1/4"         |
| AVG . Air Cons    | : 2 CFM        |
| Temperature Range | : -3°F - 140°F |
| Work Pressure     | : 40-170 PSI   |
| Max Capacity      | : 6000 CC      |



### OSP200 200ML OIL SUCTION PUMP

- Multi-purpose syringe ideal for the transfer of oils/fluids to and from vehicle components such as gearboxes and differentials.
- Translucent body allows easy inspection of oils and fluids.
- Capacity : 200ML



### OSP1500 1500ML OIL SUCTION PUMP

- Multi-purpose syringe ideal for the transfer of oils/fluids to and from vehicle components such as gearboxes and differentials.
- Translucent body allows easy inspection of oils and fluids.
- Capacity : 1500ML



### STEEL DRAIN PAN

| Item Code | Capacity (Ltr) | Size (Inchi)  |
|-----------|----------------|---------------|
| SDP1310   | 10L            | 14.5" X 19.5" |
| SDP1312   | 15L            | 17" X 25"     |
| SDP1314   | 24L            | 21" X 33"     |



### WASTE OIL STORAGE

- Polypropylene oil tray for easy drainage of engine and transmission oils.

| Item Code | Capacity (Ltr) |
|-----------|----------------|
| WOR1308   | 8L             |
| WOR1316   | 16L            |



### FLEXIBLE METAL FUNNEL

| Item Code | Tube Length |
|-----------|-------------|
| FMF6108   | 370mm       |
| FMF6109   | 630mm       |



### OP02

#### 2L OIL POT

- Application
- Max Capacity : 2 Liters



### OP04

#### 4L OIL POT

- Application:
- Max capacity 4 liters



### OF1722

#### 5PCS OIL FUNNEL

- Big funnel opening and long ATF refilling bar provide refilling work without mess & spilling.
- Efficiently improves ATF refilling process.
- Transparent lower chamber design clearly shows fluid flow process.
- Attached durable seal with NBR material ensure secure sealing.



\*Picture shown are for reference only





### HA168 MANUAL / PNEUMATIC FLUID EXTRACTOR

- Multi-function new inventen product.
- Must competitive products good looking.
- Saitable for vehicle maintenance.
- Boats market agricultural machinery.
- Max capacity 6 Liters.



### HA198 MANUAL / PNEUMATIC FLUID EXTRACTOR

- Enable manual / pneumatic oil extracting. Automatically alternated.
- Capacity : 18 Liters
- Max capacity : 90psi



### PA1011A 10L MANUAL / PNEUMATIC FLUID EXTRACTOR

#### Specification:

- Dimension : 265x315x650m/m
- Caoacity : 10L
- Weight : 4.8kg
- Oil Depletion : Manual or Air



### BFE1118 PNEUMATIC BRAKE FLUID EXTRACTOR

- One man in same step operate.
- Pneumatic extractor non spark.
- 1 Meter silicon hose with universal rubber adaptor.
- Can fit most type brake fitting.
- Fixing valve & safety cup for automatic cut-off extractor.

#### Specification :

- \* Air Inlet ..... 1/4"
- \* AVG. air Con ..... 4CFW
- \* Working Peasure ..... 70-170PSI
- \* Temperature Range ..... -3 F -140F
- \* Max Capacity ..... 2000CC



### BFE1116 PNEUMATIC BRAKE FLUID EXTRACTOR & BLEEDER KIT

- Midegt size N.W. then less 1kg easy carry & operation.
- Pneumatic extrator non-spark.
- One man in same step poerete 1meter silicon hose with universal rubber adaptor.
- Can fit most vehicle brake oil bleeder fitting fixing valve.
- Safety cup for automatic cut off extrator.



### MC7700 MINI CLEANER

- Suitable for rapid cleaning of small mechanical parts, motor part etc. easy to take, and good for wall mounting, save operating space.
- Overall Dimension :560x545x630mm
- Max solvent capacity : 14L
- Flowing rate : 1.9L/Min
- Power : 43W(120V/60HZ) ; 26W(230V50HZ)



### ELECTRICAL PART WASHER

- Recirculation Pump.
- Removable Shelf.

| Item Code | Capacity  |
|-----------|-----------|
| PW20      | 20 Gallon |
| PW40      | 40 Gallon |



### PW65 65L PART WASHER

#### Specification:

- Cleaning tank capacity : 50 Liter
- Trolley tank capacity : 60 Liter with level indicator
- Compressor supply : 6-8kgs pressure
- pressure for output solvent : 0.4-0.5kgs
- Flowing rate : 130kgs/hour
- Max working pressure : 125psi

### FC313 13PCS FLUID COUPLE

#### Attachment Specification



| Parts No | Picture | Application                      |
|----------|---------|----------------------------------|
| ATF-101  |         | FORD 1/8 - 27 ( NPT)             |
| ATF-102  |         | Universal BMW, Honda, Nisan, etc |
| ATF-103  |         | VW/Audi                          |
| ATF-104  |         | VW/Audi, Porsche                 |
| ATF-105  |         | VW/Audi, Mini cooper M10 x 1.0,  |
| ATF-106  |         | VW/Audi DSG M24 x 1.5,           |
| ATF-107  |         | VW/Audi CVT M22 x 1.5,           |
| ATF-108  |         | Mercedes M12 x 1.5,              |
| ATF-109  |         | Skoda M18 x 1.5                  |
| ATF-110  |         | Audi/VW, Skoda M30 x1.5          |
| ATF-111  |         | Universal Flexible 300mm,        |
| ATF-112  |         | Volvo 5/16 - 24 (UNF)            |
| ATF-113  |         | Toyota, Lexus M18 x 1.5          |

\*Picture shown are for reference only