



### SB22L

#### 1/2"DR SAB AIR IMPACT WRENCH

- Square Drive : 1/2"Dr Or 3/8"Dr
- Max. torque (Forward) : 400 Ft-lbs / 542 Nm
- Max. Torque (Reverse) : 450 Ft-lbs / 610 Nm
- Torque Range : 25-250 Ft-lbs / 34-340 Nm
- Standard bolt cap : 9/16 in / 14mm
- Overall Length : 5.7 in / 145 mm
- Free Speed : 12,000 rmp
- Net Weight : 3.5 lbs / 1.6kg
- Air inlet : 1/4 in



### SB33L

#### 1/2"DR SAB AIR IMPACT WRENCH

- Square Drive : 1/2"
- Max. torque (Forward) : 550 Ft-lbs / 745 Nm
- Max. Torque (Reverse) : 600 Ft-lbs / 814 Nm
- Torque Range : 25-300 Ft-lbs / 34-408 Nm
- Standard bolt cap : 9/16 in / 14mm
- Overall Length : 7.3 in / 185 mm
- Free Speed : 8,000 rmp
- Net Weight : 5.8 lbs / 2.6kg
- Air inlet : 1/4 in



### SB33

#### 1/2"DR SAB AIR IMPACT WRENCH

- Square Drive : 1/2"
- Max. torque (Forward) : 550 Ft-lbs / 745 Nm
- Max. Torque (Reverse) : 600 Ft-lbs / 814 Nm
- Torque Range : 25-300 Ft-lbs / 34-408 Nm
- Standard bolt cap : 9/16 in / 14mm
- Overall Length : 7.3 in / 185 mm
- Free Speed : 8,000 rmp
- Net Weight : 5.8 lbs / 2.6kg
- Air inlet : 1/4 in



### SB36

#### 1/2"DR SAB AIR IMPACT WRENCH

- Std. Bolt Cap. : 5/8" (16mm)
- Impact Mechanism : Twin Hammer
- Working Torque Range : 50-550 ft-lbs (68-745 Nm)
- Max. Torque : 800 ft-lbs (1085 Nm)
- Free Speed : 7,500 rpm
- Air Consumption @Load : 7.7 cfm (220 L/min)
- Length : 178mm
- Weight : 2.62kg
- Air Pressure : 90 psi (6.2 Bar)
- Air Inlet : 1/4"



### SB88L

#### 3/4"DR SAB AIR IMPACT WRENCH

- Standard bolt cap:1-1/8 in / 30 mm
- Working torque range:100~1,000ft-lbs / 135~1,500Nm
- Max. torque:1,400ft-lbs / 1,898Nm
- Free speed:7,500rpm
- Air conds.@load:10.6cfm / 300l/min
- Length:210mm
- Weight:4.2kg



### SB88L-G 3/4\"/>

- Standard bolt cap: 1-1/8 in / 30 mm
- Working torque range: 100~1,000ft-lbs / 135~1,500Nm
- Max. torque: 1,400ft-lbs / 1,898Nm
- Free speed: 7,500rpm
- Air conds.@load: 10.6cfm / 300l/min
- Length: 210mm
- Weight: 3.9kg



### SB88L-1 1\"/>

- Standard bolt cap: 1-1/8 in / 30 mm
- Working torque range: 100~1,000ft-lbs / 135~1,500Nm
- Max. torque: 1,400ft-lbs / 1,898Nm
- Free speed: 7,500rpm
- Air conds.@load: 10.6cfm / 300l/min
- Length: 210mm
- Weight: 3.99kg



### SB88L-EL 3/4\"/>

- Standard bolt cap : 1-1/8 in / 30mm
- Workinh Torque Range : 100~1,000 Ft-lb / 135~1,500 Nm
- Max. Torque : 1,200 Ft-lb / 1,627 Nm
- Free Speed : 7,500 rpm
- Air Cons.@load : 10.6 Cfm / 300 l/min
- Length : 180mm
- Weighth : 4.7kg



### SB83 3/4\"/>

- Std. Bolt Cap. : 13/16" (20mm)
- Impact Mechanism : Twin Hammer
- Working Torque Range : 50-800 ft-lbs (68-1085 Nm)
- Max. Torque : 1,100 ft-lbs (1490 Nm)
- Free Speed : 7,500 rpm
- Air Consumption @Load : 7.7 cfm (220L/min)
- Length : 178mm
- Weight : 2.68kg
- Air Pressure : 90psi (6.2 Bar)
- Air Inlet : 1/4"



### SB99 3/4\"/>

- Std.Bolt Cap.: 1-1/8" (30mm)
- Max.Torque.: 1400 ft-lb (1898NM)
- Twin Hammer Impact Mechanism



### SB966 1\"/>

- Square Driver : 1"
- Free Speed : 3000 rpm
- Max.Torque : 2500 ft-lbs / 3380 Nm
- Air Pressure : 100 psi
- Air Consumption : 9 cfm / 252 L/min
- Weight : 17 kg
- Length : 612 mm



### SB1006

#### 1/4"DR AIR DIE GRINDER

- Free Speed : 21000 rpm
- Air consumption : 20 scfm
- Length : 4-3/4" / 12.1 cm
- Weight : 13/16Lb / 0.37 kg
- Noise : 88 db
- Exhaust : Front exhaust



### SB100

#### 3/8"DR SAB AIR RATCHET

- Square Driver : 3/8"
- Free Speed : 260 rpm
- Max.Torque : 25 Nm
- Air Inlet : 1/4"
- Air Pressure : 90 psi
- Air Consumption : 140L/min
- Net Weight : 1.1 kg
- Overall Length : 160 mm



### SB101

#### 1/2"DR SAB AIR RATCHET (L/D)

- Square Driver : 1/2"
- Free Speed : 160 rpm
- Max.Torque : 70 Nm
- Air Inlet : 1/4"
- Air Pressure : 90 psi
- Air Consumption : 180L/min
- Net Weight : 1.2 kg
- Overall Length : 260 mm
- Planet Gear Mechanism : 3 Gear



### SB102

#### 1/2"DR AIR RATCHET

- Square Driver : 1/2"
- Free Speed : 160 rpm
- Max.Torque : 82 Nm
- Air Inlet : 1/4"
- Air Pressure : 90 psi
- Air Consumption : 200L/min
- Net Weight : 1.1 kg
- Overall Length : 229 mm



### SB103

#### 1/2"DR SAB AIR RATCHET (H/D)

- Square Driver : 1/2"
- Free Speed : 160 rpm
- Max.Torque : 100 Nm
- Air Inlet : 1/4"
- Air Pressure : 90 psi
- Air Consumption : 200L/min
- Net Weight : 1.2 kg
- Overall Length : 270 mm
- Planet Gear Mechanism : 2 Gear
- Exhaust system : rear



### SB388

#### MINI AIR BODY SAW

- Free Speed : 7500 bpm
- Noise : 80 dba
- Stroke : 5.5 mm
- Air Consumption : 0.2 min
- Light : 155 mm
- Weight : 402 g
- Use Pressure : 90 psi



### SB306

#### SAB AIR BODY SAW

- Air Pressure : 90
- Air Inlet : 1/4"
- Air Consumption : 1 Min
- Noise : 83 dba
- Weight : 0.8 kg / pc



### SB3838S

#### 3/8" SAB AIR IMPACT WRENCH (L/D)

- Also known as butterfly type, handy for the confined and cramped spaces.
- Hand touch forward-reverse switch plate for convenient operation.
- 8-position power regulator for the desired speed.
- Light torque for the light service applications

#### Specification:-

- Square Driver : 3/8"
- Free Speed : 9500 rpm
- Max.Torq : 75 ft-lbs/102Nm
- Air Inlet : 1/4"
- Air Pressure : 90 psi / 6.3kg/cm<sup>2</sup>
- Air Consumption : 312 L/min
- Net Weight : 1.14 kg
- Overall Length : 142 mm



### SB1066

#### 3/8" REVERSIBLE AIR DRILL

- Free Speed : 1800rpm
- Air Consumption : 10 cfm/ 283 L/min
- Length : 7-7/8" / 20cm
- Weight : 2.40 lb / 1.09 kg
- Exhaust : Side Exhaust
- Overall Length : 6.97 In / 177mm
- Operating Air Pressure : 90 psi / 6.3 kg/cm<sup>2</sup>



### HOSE REEL

- Automatic Hose Reel For Compressor.
- Heavy Duty Reinforced steel construction with paint coating.

Item Code	Hose I.D	Max Pressure	Length	N.W	Material
HR0815	5/16" (8mm)	3000 Psi	15 Meter	6.5 Kg	PU Baid
HR0912	3/8" (9mm)	3000 Psi	12 Meter	6.5 Kg	PU Baid



### MAC824

#### MINI AIR COMPRESSOR

- Special design for car but is used multi-fuctional (air Mattersses, athletic ball, recreational inflatable, etc.)
- Always pump your tires until the assigned pressure level is reached. exceed the level.)
- Never leave the compressor in operation without supervision.
- Do not use for more than 15 minutes to avoid overheating. Never continue operation within 10 minutes cooling.
- Always remove the compressor with the open valve.

#### Specification:-

- Power Required : DC 12Volt
- Net Weight : 1.20Kgs



### SB311

#### HEAVY DUTY AIR HAMMER KIT

- Stroke Speed : 3000 bpm
- Air Inlet : 1/4"
- Piston Stroke : 60mm
- Length : 175mm
- Net Weight : 1.7kg
- Air Cons : 187 L/min
- Hose Inlet :: 3/8"
- Piston Diameter : 3/4"

### SB315

#### HEAVY DUTY AIR HAMMER KIT


- Stroke Speed : 2100 bpm
- Air Inlet : 1/4"
- Piston Stroke : 90mm
- Length : 220mm
- Net Weight : 2.0kg
- Air Cons : 210 L/min
- Hose Inlet :: 3/8"
- Piston Diameter : 3/4"



### SB118

#### AIR VALVE LAPPER

- Stroke Speed : 3000bpm
- Air inlet : 1/4"
- External dimension : 153.5 x 52mm
- Weight : 1.5kgs
- Air pressure : 90psi
- Air consumption : 100L / min
- 4pcs rubber sucker 16 20 30 35mm



\*Picture shown are for reference only



### IGK401 INFLATOR GAUGE KIT

- Air inflator provides user with easy and controlled inflation
- Cast in alloy body with H-D brass valves.
- With 438mm Hose, 3" pressure gauge, and easy-to-read
- 3 function in 1 : Fill air, release air and gauge pressure
- 0 to 240psi / 0 to 16 bar



### IGK501 INFLATOR GAUGE KIT

- **Specifications**
- Body Length : 270mm
- Air Hose : 350mm
- Overall Length : 650mm
- Range : 0-1100 KPA (0-160 psi)
- Air Supply Minium : 90PSI
- Air Supply Maximum : 200PSI
- Inlet : 1/4 BSP Female



### FR503 3/8" AIR FILTER REGULATOR

- Port Size (PT, NPT) : 3/8"
- Filter Element : 5  $\mu$ m
- Max Input Pressure (PSI) : 215
- Max Output Pressure (PSI) : 7 ~ 142
- Max Flow ( $\ell$ /min) : 3000
- Operating Temp Range : 5°C ~ 60°C
- Drain Capacity : 55ml
- Oil Capacity : 80ml
- Recommendable Lubricants : ISO VG-32



### FRL503 3/8" AIR FILTER REGULATOR LUBRICANTS

- Port Size (PT, NPT) : 3/8"
- Filter Element : 5  $\mu$ m
- Max Input Pressure (PSI) : 215
- Max Output Pressure (PSI) : 7 ~ 142
- Max Flow ( $\ell$ /min) : 3000
- Operating Temp Range : 5°C ~ 60°C
- Drain Capacity : 55ml
- Oil Capacity : 80ml
- Recommendable Lubricants : ISO VG-32



### F906 3/4" AUTO AIR FILTER

- The filter / regulator / lubricant is a three part system. The filter is designed to remove most liquid and solid particles from the air supply. The self-removing pressure regulator is used to adjust the outlet pressure. The lubricant provides oil to the air tool and increases the life of the tool.

#### Specifications

- Max. Temperature : 140°F
- Air Inlet / outlet : 1", 3/4"
- Gauge Ports : 1/4"
- Max. Pressure : 300PSI



### F706 3/4" AUTO AIR FILTER

- The filter / regulator / lubricant is a three part system. The filter is designed to remove most liquid and solid particles from the air supply. The self-removing pressure regulator is used to adjust the outlet pressure. The lubricant provides oil to the air tool and increases the life of the tool.

#### Specifications

- Max. Temperature : 140°F
- Air Inlet / outlet : 1/2", 3/4"
- Gauge Ports : 1/4"
- Max. Pressure : 250PSI



### AD113

#### SAB Air Duster (230mm)

- Suitable for cleaning any kind of machinery and equipment.
- Max. pressure required 150 psi.
- Standard volume required 100 l/min.
- Overall length : 230mm



### AD118

#### SAB Air Duster (395mm)

- Suitable for cleaning any kind of machinery and equipment.
- Max. pressure required 150 psi.
- Standard volume required 100 l/min.
- Overall length : 395mm



### AC02

#### 2WAY AIR COUPLE

- Lightweight and compact in size.
- Easy installation and storage.
- Accessory pressure gauge and drain valve ease piping control.
- Body : Aluminum
- Working Pressure : 10 kgf / cm<sup>2</sup>
- Maximum Pressure : 15 kgf / cm<sup>2</sup>
- Temp.Range : -20°C ~ + 80°C
- Size : 1/4" (20Type)



### AC03

#### 3WAY AIR COUPLE

- Lightweight and compact in size.
- Easy installation and storage.
- Accessory pressure gauge and drain valve ease piping control.
- Body : Aluminum
- Working Pressure : 10 kgf / cm<sup>2</sup>
- Maximum Pressure : 15 kgf / cm<sup>2</sup>
- Temp.Range : - 20°C ~ + 80°C
- Size : 1/4" (20Type)



Item Code	Description
SB20PM	1/4" (pt)
SB30PM	3/8" (pt)
SB40PM	1/2" (pt)



Item Code	Description
SB20PH	5/16" (hose)
SB30PH	3/8" (hose)
SB40PH	1/2" (hose)



Item Code	Description
SB20PF	1/4" (pt)
SB30PF	3/8" (pt)
SB40PF	1/2" (pt)



Item Code	Description
SB20SH	5/16" (hose)
SB30SH	3/8" (hose)
SB40SH	1/2" (hose)



Item Code	Description
SB20SF	1/4" (pt)
SB30SF	3/8" (pt)
SB40SF	1/2" (pt)



Item Code	Description
SB20SM	5/16" (hose)
SB30SM	3/8" (hose)
SB40SM	1/2" (hose)

\*Picture shown are for reference only